

## The Poleboss™ System

A safe and efficient way to install your distribution services

### POLEBOSS™ SYSTEM

#### POLEBOSS PULLER UNIT

Performance: 450 kg (1000 lbs) linepull @ 120 m/min (400 ft/min) based on hydraulic supply of 15 gpm @ 2000 psi
Precise metering spring to neutral control valve
Linepull limiting tension control valve
Hydraulic pressure gauge
Anti-rotation clutch
2 ratchet type web binder straps
Manual rope levelwind
Hydraulic quick disconnects

 Weight
 98 kg (215 lbs)

 Weight (with reels)
 154kg (340 lbs)

 Length
 686 mm (27")

 Width
 457mm (18")

 Height
 1016 mm (40")





#### PAYOUT SPINDLE

- · Galvanized steel frame construction
- · Hot stick adjustable disc brake
- 140 kg. (300 lbs) maximum breaking force
- · Ratchet type web binder strap
- · Payout spindle weight 16 kg (35 lbs.)

#### ROPE AND REEL

- Reel capacity: 915 m (3000 ft) of 10mm (3/8") rope
- · Reel weight: 54 kg (119 lbs) without rope

# OUR PEOPLE CARE... OUR EQUIPMENT IS THE PROOF

## TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE