

DRUM PULLER



SPECIFICATIONS

Model DP-60

Maximum continuous torque
Maximum linespeed
Linepull*

2033 daNm (180,000 in.lbs)
6.4 km/h (4 mph)
2720 daN (6000 lbs)

Model DP-70

Maximum continuous torque
Maximum linespeed
Linepull*

2370 daNm (210,000 in.lbs)
5.5 km/h (3.4 mph)
3174 daN (7000 lbs)

Model DP-60 / DP-70

Maximum reel dimensions
Reel shaft diameter
Engine (diesel)
Weight (wo reel/rope)
Length
Width

1.8 m x 1.3 m (72" x 52")
89 mm (3-1/2")
97 kW (130 hp)
4150 kg (9150 lbs)
5.64 m (222")
2.44 m (96")

* Linepull is shown at 762 mm (30") radius

STANDARD EQUIPMENT

Fully hydraulic drive system
Infinitely variable speed and linepull control
Automatic overpull protection system
Water-cooled diesel engine
Spring applied / hydraulic release drive brake
Tandem axle trailer with highway lighting
Single front and two rear jacks
Hydraulic levelwind
Reel shaft free wheeling disconnect 406 mm (16") diameter bronze disc
reel brake
Quick change reel shaft system

OPTIONS

Model 6052 (1524 mm x 1320 mm) reel
Model 7252 (1829 mm x 1320 mm) reel
Air/hydraulic trailer brakes

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE