

BULLWHEEL PULLER



SPECIFICATIONS

Maximum linepull	4000 daN (8990 lbs)
Maximum linespeed	5 km/h (3.1 mph)
Bullwheel diameter	406 mm (16")
Maximum rope diameter	16 mm (5/8")
Power (Diesel)	48 kW (65 hp)
Weight (Approx.)	1678 kg (3700 lbs)
Length (Approx.)	2590 mm (102")
Width (Approx.)	1828 mm (72")
Height (Approx.)	1524 mm (60")

STANDARD EQUIPMENT

Fully hydraulic drive system
 Infinitely variable speed and linepull control
 Direct drive bullwheels with totally enclosed oil bath, gearbox
 Automatic overpull protection system
 Diesel power unit
 Spring applied / hydraulic released brakes
 Single axle trailer
 Hydraulic oil cooler
 Console cover



OPTIONS

Auxiliary hydraulic circuit for separate reel winder
 Tower fairlead
 Integral self-loading reel winder for reel sizes up to 1400 mm (55") diameter x 600 mm (24") wide x 2000 kg (4400 lbs), includes automatic diamond leadscrew levelwind

**OUR PEOPLE CARE ...
 OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE