

V-GROOVE PULLER



This puller is ideal for re-conductoring projects where the old conductor or earthwire is utilized to directly pull in the new conductor or OPGW.

SPECIFICATIONS

| | |
|--------------------|---------------------|
| Maximum linepull | 4000 daN (8990 lbs) |
| Maximum linespeed | 5 km/h (3.1 mph) |
| Bullwheel diameter | 1375 mm (54") |
| Power (Diesel) | 44.5 kW (60 hp) |
| Weight (Approx.) | 2265 kg (4995 lbs) |
| Length (Approx.) | 3581 mm (141") |
| Width (Approx.) | 1524 mm (60") |
| Height (Approx.) | 2211 mm (87 1/16") |

EXCLUSIVE FEATURE

Canted Bullwheel design

- Use old earthwire or conductor as pulling rope
- reduce bending stress on old conductor
- V-groove will pass conductor joints
- Linings are replaceable

STANDARD FEATURES

Fully hydraulic drive, direct drive system
 Infinitely variable speed control
 Automatic overpull protection system
 Oil cooled diesel power unit
 Spring applied / hydraulic release brakes
 Auxiliary hydraulic circuit to operate separate reel winder
 Hydraulic oil cooler
 Single axle trailer on high flotation tires
 3 roller tail fairlead
 Console cover

OPTIONS

Highway lighting
 Tower fairlead

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE