

**SELF-LOADING REEL CARRIER**

**SPECIFICATIONS**

The Timberland Model RCSL 600 156 x 108 is designed to transport a single cable reel and release or wind in cable under controlled conditions, depending on the options selected.

**DIMENSIONS**  
(approximate)

Length	7595 mm (299")
Width	3785 mm (149") loaded 2743 mm (108") travel
Height	3962 mm (156") top of reel
Weight (w/o reel)	6,123 kg (13,500 lbs)
Spindle diameter	153 mm (6")
Maximum reel diameter	3962 mm (156")
Maximum reel width	2743 mm (108")
Maximum reel weight	27,215 kg (60,000 lbs)

**STANDARD EQUIPMENT**

Bronze bushings on reel shaft  
 Shaft locating collars  
 Self-loading by hydraulic cylinders located on each side of the reel shaft  
 Manual locking pins in travel position

Engine (Diesel) 14 kW (19 hp)

**OPTIONS**

Hydraulic reel shaft rewind (rim drive)  
 Tool box 356 mm x 356 mm x 610 mm (14" x 14" x 24")

**OUR PEOPLE CARE ...  
OUR EQUIPMENT IS THE PROOF**

**TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE**